



Irrigatore AB

Descrizione:

Modello a impatto a funzionamento circolare.

Attacco 1" femmina

Boccaglio singolo

Peso 0,64 Kg

TABELLA TECNICA



Ø Boccaglio mm	Pressione all'irrigat. bar	Gittata massima m	Portata erogata Lt/sec
4	1,5	12,5	0,20
	2	13	0,26
	3	14	0,31
	4	15	0,36
	5	16	0,40
4,5	1,5	13	0,25
	2	13,5	0,29
	3	14,5	0,36
	4	15,5	0,43
	5	16,5	0,49
5	1,5	13,5	0,30
	2	14	0,36
	3	15	0,44
	4	16	0,50
	5	17	0,56
6	1,5	14	0,45
	2	14,5	0,51
	3	15,5	0,63
	4	17	0,73
	5	18	0,82
7	1,5	14,5	0,62
	2	15	0,70
	3	16	0,86
	4	17,5	1,0
	5	18,5	1,11
8	1,5	15	0,81
	2	15,5	0,92
	3	17	1,13
	4	18,5	1,30
	5	19	1,46

R25SF | R25S | R25 | R25S teso | R18S | R18 | R15S | R15 | R6 | V2 | GT | GTS | REX | R3S | R3 | R3V | MICRO

◀ INDIETRO



**IDROMECCANICA
ROSSI**
Irrigatori - Sprinklers

TORNA SU ↗

